

Uni-Body W-100 Spray-All

MODEL # 975070

OVERVIEW

The Uni-Body W-100 Spray-All is a water-driven, high volume spray applicator for applying chemical solutions to a variety of surfaces. This venturi injection system uses standard city water pressure (35 - 125 PSI) to draw and blend chemical concentrate into the water stream. Precision metering tips are used to create an accurately diluted solution which is projected through the discharge hose and fan nozzle as a uniform "flooding" spray. With a flow rate of around 4 gallons per minute, this unit is great for spraying down large areas or objects.

Key Features

- The machined polypropylene uni-body design is both compact and cost-effective
- Creates a high volume, flooding spray
- Designed for spraying large surfaces and objects
- Fan pattern nozzle for even coverage
- Chemical resistant wetted components ensure years of outstanding performance with minimal maintenance
- Use it anywhere 35-125 PSI water is available
- Available with a stainless steel mounting bracket (#970270)
- See other Lafferty Spray-Alls and more chemical applicators in [Catalog 1](#)

Includes

- Machined polypropylene injector body
- Inlet and discharge ball valves
- 20 color-coded metering tips for setting dilution ratios
- 50' discharge hose, polypropylene wand and stainless steel fan nozzle

OPTIONS

Stainless Steel Hose Racks

Large Stainless Steel Hose Rack # 224150

Stainless Steel Jug Racks

1 Gallon Round/Square # 224200

1 Gallon Round/Square Locking # 224200-L

2 ½ Gallon (8 ½" x 10 ½") # 224210

5 Gallon Round/Square Locking (12" x 12") # 224214

5 Gallon Round/Square (12" x 12") # 224215

Safe Flow Lid™ for 1 Gallon Jugs

Lid, Suction Tube, and Strainer # 709101

Alternate Check Valve - EPDM Standard

Check Valve, Chemical, PP/Viton, 1/4" # 491315

APPLICATIONS

- Agriculture/Horticulture
- Animal Health
- Food & Beverage
- Industrial
- Janitorial/Sanitation
- Pharm/Bio
- Supermarkets
- And Many Other Applications!



REQUIREMENTS

Chemical Concentrate

Water

Temperature up to 160°F
 Pressure 35 to 125 PSI
 Flow 4.0 GPM @ 40 PSI
 Supply Line 3/4"

Hose

1/2" ID x 50'

Nozzle

40100

Dilution Ratio Range

914:1 to 9:1 @ 40 PSI

