

Portable Rinse / LC Foam Hose Drop Station

MODEL # 915840

OVERVIEW

The Portable Rinse/LC Foam Hose Drop Station is a medium volume foam applicator featuring an all stainless steel cart assembly. It will project foaming chemicals on to any surface up close or at a distance and rinse through the same hose. This venturi injection system uses standard city water pressure (35 - 125 PSI) to draw and blend chemical concentrate into the water stream to create an accurately diluted solution. Rich, clinging foam is created by injecting compressed air into the solution to greatly increase volume and coverage ability. The foam is then projected through the discharge hose and fan nozzle at distances up to 12 feet. Switch to the powerful 4-hole nozzle and rinse at full pressure.

Key Features

- Foam and rinse through a single hose
- Designed for foaming and rinsing medium to large surfaces
- Projects a medium volume of rich, clinging foam which increases chemical contact time and effectiveness
- Foaming expands the chemical and reduces over-application by providing visual assurance of coverage
- Fan pattern foam nozzle for fast coverage (up to 12' range)
- Covers up to 500 sq ft (46.5 sq m) in 2 minutes
- Adjustable foam consistency (wet/dry)
- Stainless steel and polypropylene wetted components ensure years of trouble-free performance
- Industrial-strength design holds up in tough environments
- Available as a wall-mounted unit (#915118)
- See other configurations of Lafferty city water pressure foamers in [Catalog 1](#)

Includes

- All stainless steel 4-wheel cart with integrated hose rack
- Non-marking tires with stainless steel swivel casters
- Stainless steel, round, 5 gallon jug rack (square optional)
- Machined polypropylene foamer body
- Stainless steel inlet and discharge ball valves
- 20 color-coded precision metering tips to set dilution ratios
- 40' discharge hose and quick connect fittings
- Quick connect polypropylene foam wand with fan nozzle
- Quick connect stainless steel 4-hole rinse nozzle

OPTIONS

5 Gallon Pail

Pail, 5 Gallon Round W/ Suction Stem # 709105

Safe Flow Lid™ for 1 Gallon Jugs

Lid, Suction Tube, and Strainer # 709101

Square Jug Rack Conversion

Specify Round or Square Jug Racks at time of order

Alternate Check Valves - EPDM Standard

Check Valve, Chemical, PP/Viton, 1/4" # 491315

Check Valve, Air, SS/Viton, 1/4" # 491306

APPLICATIONS

- Agriculture/Horticulture
- Animal Health
- Vehicle Wash
- Dairy
- Food & Beverage
- Hatchery
- Industrial
- And Many Other Applications!



REQUIREMENTS

Water

Temperature up to 160°F
 Pressure 35 to 125 PSI
 Flow 7.2 GPM @ 40 PSI
 Supply Line 3/4"

Compressed Air

up to 3 CFM

Hose

Rinse 3/4" ID x 40'
 Foam 3/4" ID x 40'

Nozzle

Rinse 4 Hole Rinse Nozzle
 Foam 50250

Dilution Ratio Range @ 40 PSI

Foam 306:1 to 6:1

Lafferty
EQUIPMENT MANUFACTURING INC.

1.501.851.2820 or 1.800.999.2820
laffertyequipment.com

