

Rinse / A-25 Airless Foam Hose Drop Station

MODEL # 915918

OVERVIEW

The Rinse/A-25 Airless Foam Hose Drop Station is a combination medium volume foam applicator for projecting foaming chemicals on to any surface up close or at a distance and for rinsing, without compressed air. This venturi injection system uses city water pressure (35 - 125 PSI) to draw and blend chemical concentrate into the water stream to create an accurately diluted solution. The solution then flows through the discharge hose to the "airless" foam wand which draws in atmospheric air to create and project wet, clinging foam at distances up to 6 feet. Rinse at full pressure through a separate hose and unique, powerful 4-hole nozzle.

Key Features

- No compressed air required
- Designed for foaming & rinsing medium to large surfaces
- Projects wet, clinging foam which increases chemical contact time and effectiveness
- Foaming expands the chemical and reduces over-application by providing visual assurance of coverage
- Projects foam up to 6' (depending on water pressure)
- All stainless steel and polypropylene wetted components ensure years of trouble-free performance
- Industrial-strength design holds up in tough environments
- Available without a rinse function (#970525)
- See other configurations of Lafferty city water pressure foamers in [Catalog 1](#)

Includes

- Stainless steel mounting bracket
- Machined polypropylene foamer body
- Stainless steel inlet and discharge ball valves
- 20 color-coded precision metering tips to set dilution ratios
- 50' foam hose & machined polypropylene airless foam wand
- 50' rinse hose & stainless steel 4-hole nozzle

OPTIONS

Stainless Steel Hose Racks

Large Stainless Steel Hose Rack # 224150

Stainless Steel Jug Racks

Jug Rack, SS, 1 Gallon, Round/Square # 224200

Jug Rack, SS, 2 1/2 Gallon # 224210

Jug Rack, SS, 5 Gallon, Round/Square # 224215

Safe Flow Lid™ for 1 Gallon Jugs

Lid, Suction Tube, and Strainer # 709101

Stainless Steel Airless Foam Wand

Wand, SS, Airless Foam, A-25SS # 536625SS

Alternate Check Valve - EPDM Standard

Check Valve, Chemical, PP/Viton, 1/4" # 491315

APPLICATIONS

- Animal Health
- Dairy
- Food & Beverage
- Hatchery
- Industrial
- Janitorial/Sanitation
- Pharm/Bio
- Supermarkets
- And Many Other Applications!



REQUIREMENTS

Water

Temperature up to 160°F
 Pressure 35 to 125 PSI
 Flow 7.2 GPM @ 40 PSI
 Supply Line 3/4"

Hose

Rinse 3/4" ID x 50'
 Foam 1/2" ID x 50'

Nozzle

Rinse 4 Hole Rinse Nozzle
 Foam A-25 Airless Foam Wand

Dilution Ratio Range @ 40 PSI

Foam 306:1 to 6:1

Lafferty
EQUIPMENT MANUFACTURING INC.

1.501.851.2820 or 1.800.999.2820

laffertyequipment.com