

W-20SS Sanitize / Rinse / Hyper SS Foam Hose Drop Station

MODEL # 917227

OVERVIEW

The W-20SS Sanitize / Rinse / Hyper SS Foam Hose Drop Station is a combination applicator for quickly applying one chemical as foam at 3.3 GPM @ 700 PSI, another as a sanitizing spray and for rinsing. This stainless steel venturi injection system uses high water pressure (400 - 1000 PSI) to draw and blend chemical concentrates into the water streams to create accurately diluted solutions using precision metering tips to control chemical usage. Rich, clinging foam is created by injecting compressed air into the foaming solution to greatly increase volume and coverage ability. The foaming solution then flows through the foam hose and is projected through the fan nozzle at distances up to 13 feet. Rinse and sanitize using the second hose, trigger gun and fan nozzle.

Key Features

- Designed to foam, rinse and sanitize medium to large sized surfaces and objects
- Projects a substantial volume of rich, clinging foam which increases chemical contact time and effectiveness
- Foaming expands the chemical and reduces over-application by providing visual assurance of coverage
- Fan pattern foam nozzle for fast coverage (up to 13' range)
- Covers up to 500 sq ft (46.5 sq m) in 1.5 minutes
- Optional zero degree nozzle for increased range
- Adjustable foam consistency (wet/dry)
- Stainless steel components ensure durability and years of trouble-free performance
- Available without a rinse function (#917120)
- Available with a lower flow rate (#918227)
- See other high water pressure foamers in [Catalog 3](#)

Includes

- Stainless steel mounting bracket
- Stainless steel inlet ball valves
- Machined stainless steel foamer and sanitizer bodies
- 20 color-coded precision metering tips to set dilution ratios
- 50' foam hose, polypropylene open flow wand & fan nozzle
- 50' rinse/sanitize hose, trigger gun, wand & fan nozzle

OPTIONS

Stainless Steel Hose Racks

Large Stainless Steel Hose Rack # 224150

Stainless Steel Jug Racks Available

Safe Flow Lid™ for 1 Gallon Jugs

Lid, Suction Tube, and Strainer # 709101

Alternate Check Valve - EPDM Standard

Check Valve, Chemical, SS, Viton, 1/4" # 491324-V

Alternate Check Valves - EPDM Standard

Check Valve, Chemical, PP/Viton, 1/4" # 491315

Check Valve, Air, SS/Viton, 1/4" # 491306

APPLICATIONS

- Food & Beverage
- Agriculture/Horticulture
- Animal Health
- Industrial
- And Many Other Applications!



REQUIREMENTS

Chemical Concentrate

Water

Temperature up to 180°F
 Pressure 400 to 1000 PSI
 Flow 8.4 GPM @ 700 PSI
 Supply Line 3/8"

Compressed Air

up to 5 CFM

Hose

Sanitize 3/8" ID x 50'
 Rinse 3/8" ID x 50'
 Foam 3/4" ID x 50'

Nozzle

Sanitize 2520
 Rinse 2520
 Foam 65300

Dilution Ratio Range @ 700 PSI

Sanitize 711:1 to 7:1
 Foam 756:1 to 8:1



536500 Insulator for 1/4" SS Wand
 Insulates hands from hot or cold extremes and provides comfortable secure grip.



1.501.851.2820 | 1.800.999.2820
www.laffertyequipment.com