W-20SS Spray-All

MODEL # 918054

OVERVIEW

The W-20SS Spray-All is a water-driven spray applicator for applying chemical solutions to a variety of surfaces at 3.11 GPM @ 700 PSI. This stainless steel venturi injection system uses high water pressure (400 - 1000 PSI) to draw and blend chemical concentrate into the water stream using precision metering tips. The accurately diluted solution is then projected through the discharge hose, trigger gun, wand and fan nozzle.

Key Features

- Designed for spraying down medium to large sized surfaces and objects
- Projects a chemical spray in a fan pattern for quick application (3.11 GPM @ 700 PSI)
- All stainless steel components ensure years of outstanding performance with minimal maintenance
- Industrial-strength design holds up in tough environments
- Available with a lower flow rate (#918050)
- See other Lafferty high water pressure chemical applicators in Catalog 3

Includes

- · Stainless steel mounting bracket
- · Machined stainless steel injector body
- 20 color-coded precision metering tips to set dilution ratios
- 50' discharge hose, trigger gun, wand & fan nozzle



Stainless Steel Hose Racks

Large Stainless Steel Hose Rack # 224150

Stainless Steel Jug Racks

Jug Rack, SS, 1 Gallon, Round/Square# 224200Jug Rack, SS, 2 1/2 Gallon# 224210Jug Rack, SS, 5 Gallon, Round/Square# 224215

Safe Flow Lid™ for 1 Gallon Jugs

Lid, Suction Tube, and Strainer # 709101

Alternate Check Valve - EPDM Standard

Check Valve, Chemical, SS, Viton, 1/4" # 491324-V

APPLICATIONS

- Food & Beverage
- Agriculture/Horticulture
- Animal Health
- Dairy
- Hatchery
- Industrial
- Metal Processing
- Military
- Paper Mill
- Pharm/Bio
- And Many Other Applications!





REQUIREMENTS

Chemical Concentrate

Water

Temperature up to 180°F
Pressure 400 to 1000 PSI
Flow 3.11 GPM @ 700 PSI

Supply Line 3/8"

Hose 3/8" ID x 50'

Nozzle 2520

Dilution Ratio Range 711:1 to 7:1 @ 700 PSI

