

# Pump Fed XV Foamer

MODEL # 919305

## OVERVIEW

The Pump Fed XV Foamer is a high volume foam applicator for projecting ready-to-use foaming chemicals on to any surface up close or at distances up to 15 feet (25 feet with zero degree nozzle). This unit receives ready-to-use chemical solution from a central chemical feed system and creates rich, clinging foam by injecting compressed air into the solution to greatly increase volume and coverage ability. A high volume of foam is then projected through the discharge hose and foam nozzle.

## Key Features

- Receives ready-to-use chemical solution from a central chemical feed system
- Designed for foam cleaning large surfaces and areas
- Projects a high volume of rich, clinging foam which increases chemical contact time and effectiveness
- Foaming expands the chemical and reduces over-application by providing visual assurance of coverage
- Fan pattern nozzle for quick coverage (up to 15' range)
- Covers up to 500 sq ft (46.5 sq m) in 1 minute
- Zero degree nozzle for up to 25' range
- Adjustable foam consistency (wet/dry)
- Chemical resistant wetted components ensure years of outstanding performance with minimal maintenance
- Industrial-strength design holds up in tough environments
- Available with a lower flow rate (#920105)
- See other pump-fed applicators in [Catalog 5](#)
- Design the optimal central chemical feed system with the [Lafferty Pump-Fed Central System Calculator](#)

## Includes

- Stainless steel mounting bracket
- Stainless steel inlet and discharge ball valves
- Machined polypropylene foamer body
- 50' discharge hose
- Polypropylene foam wand with fan and zero degree nozzles

## OPTIONS

### Stainless Steel Hose Racks

Large Stainless Steel Hose Rack # 224150

### Foam Solution Check Valves & Strainer

Check Valve, PP, 1/2" (EPDM) # 491409

Check Valve, PP, 1/2" (Viton) # 491411

Check Valve, 316SS, 1/2", MF (Teflon) # 491348SS-T

Strainer, "Y", SS, 1/2" MF # 150350-1

### Alternate Air Check Valve - EPDM Standard

Check Valve, Air, SS, 1/4" MM (Viton / Hast) # 491306

### Stainless Steel Foam Wand, HV (Upgrade)

Convert PP Wand to SS (New Units) # 536605-X

## APPLICATIONS

- Food & Beverage
- Agriculture/Horticulture
- Animal Health
- Vehicle Wash
- Dairy
- Hatchery
- Industrial
- Military
- Paper Mill
- Pharm/Bio
- And Many Other Applications!



## REQUIREMENTS

### Ready-to-Use Chemical Solution

Temperature up to 160°F  
 Pressure 35 to 100 PSI  
 Flow 4 GPM @ 40 PSI  
 Supply Line 1/2"

### Compressed Air

up to 6 CFM

### Hose

1" ID x 50'

### Nozzle

00400 & 50400