

## MODEL # 925505

## **OVERVIEW**

The 5 Gallon LV Tank Foamer is a low-volume venturi foam applicator that uses compressed air to pressurize the water in the tank to create the water pressure to draw and blend chemical concentrate into the water stream. Compressed air is injected into the solution which is projected as a low-volume of rich, clinging foam on to any surface up close or at distances up to 9 feet. Each fill provides 7 minutes of continuous foaming.

## **Key Features**

- Only water is held in the stainless steel tank and compressed air pressurizes the water to drive the venturi foamer
- No pre-dilution of chemical is required and no chemical enters the tank
- Designed for more controlled foaming in smaller areas
- Projects a low volume of rich, clinging foam which increases chemical contact time and effectiveness
- Foaming expands the chemical and reduces over-application by providing visual assurance of coverage
- Fan pattern nozzle for quick coverage (up to 9' range)
- Adjustable foam consistency (wet/dry)
- · No moving parts, virtually no maintenance required
- Available with a 15 gallon tank (#925515)
- Available as an internal tank foamer (#925905)
- See all Lafferty tank foamers and sprayers in Catalog 4

#### Includes

- All stainless steel 2-wheel cart with non-marking tires and integrated hose rack
- 5 gallon, stainless steel, NSDA rated pressure tank
- Stainless steel, 1 gallon, chemical jug rack
- Machined polypropylene foamer body
- 20 color-coded precision metering tips to set dilution ratios
- Stainless steel pressure relief pop-off valve
- 25' discharge hose, stainless steel discharge ball valve, polypropylene foam wand and fan nozzle

## **OPTIONS**

Safe Flow Lid™ for 1 Gallon Jugs

Lid, Suction Tube, and Strainer # 709101

Alternate Check Valves - EPDM Standard

Check Valve, Chemical, PP/Viton, 1/4" # 491315 Check Valve, Air, SS/Viton, 1/4" # 491306





# **REQUIREMENTS**

Chemical Concentrate Water to Fill Tank

Compressed Air up to 4 CFM

Nozzle 80150

**Dilution Ratio Range** 183:1 to 0:1 @ 60 PSI

#### **APPLICATIONS**

- Food & Beverage
- Agriculture/Horticulture
- Animal Health
- Vehicle Wash
- Dairy
- Hood & Vent
- Industrial
- Janitorial/Sanitation
- Military
- Pharm/Bio
- And Many Other Applications!











