

# 15 Gallon LV Tank Foamer

MODEL # 925515

## OVERVIEW

The 15 Gallon LV Tank Foamer is a low-volume venturi foam applicator that uses compressed air to pressurize the water in the tank to create the water pressure to draw and blend chemical concentrate into the water stream. Compressed air is injected into the solution which is projected as a low-volume of rich, clinging foam on to any surface up close or at distances up to 9 feet. Each fill provides approximately 20 minutes of continuous foaming time.

## Key Features

- Only water is held in the stainless steel tank and compressed air pressurizes the water to drive the venturi foamer
- No pre-dilution of chemical is required and no chemical enters the tank
- Designed for more controlled foaming and extended foaming time in smaller areas
- Projects a low volume of rich, clinging foam which increases chemical contact time and effectiveness
- Foaming expands the chemical and reduces over-application by providing visual assurance of coverage
- Fan pattern nozzle for quick coverage (up to 9' range)
- SafeFlow™ Lid to keep out chemical contaminants, reduce odors, and prevent spills.
- Adjustable foam consistency (wet/dry)
- No moving parts, virtually no maintenance required
- Available as an internal tank foamer (#925916)
- See all Lafferty tank foamers and sprayers in [Catalog 4](#)

## Includes

- All stainless steel 2-wheel cart with non-marking tires and integrated hose rack
- 15 gallon, stainless steel, NSDA rated pressure tank
- Stainless steel, 1 gallon, chemical jug rack
- Machined polypropylene foamer body
- 20 color-coded precision metering tips to set dilution ratios
- SafeFlow™ Lid for 1-gallon jug
- Stainless steel pressure relief pop-off valve
- 25' discharge hose, stainless steel discharge ball valve, polypropylene foam wand and fan nozzle

## OPTIONS

### Alternate Check Valves - EPDM Standard

Check Valve, Chemical, PP/Viton, 1/4"	# 491315
Check Valve, Air, SS/Viton, 1/4"	# 491306



## REQUIREMENTS

<b>Chemical Concentrate</b>	
<b>Water to Fill Tank</b>	
<b>Compressed Air</b>	up to 5 CFM
<b>Nozzle</b>	80150
<b>Dilution Ratio Range</b>	183:1 to 5:1 @ 60 PSI

## APPLICATIONS

- Food & Beverage
- Agriculture/Horticulture
- Animal Health
- Vehicle Wash
- Dairy
- Hood & Vent
- Industrial
- Janitorial/Sanitation
- Military
- Pharm/Bio
- And Many Other Applications!



**Lafferty**  
EQUIPMENT MANUFACTURING LLC  
CFS TECHNOLOGIES

1.501.851.2820 | 1.800.999.2820  
www.laffertyequipment.com