

5 Gallon Internal Tank Foamer

MODEL # 925905

OVERVIEW

The Internal 5 Gallon Tank Foamer is a low-volume foam applicator with an all stainless steel cart assembly for applying ready-to-use foaming chemicals. Connect compressed air to pressurize the 316L stainless steel ASME rated tank and to inject air into the solution to greatly increase volume and coverage ability. A low-volume of rich, clinging foam is projected on to any surface up close or at distances up to 9 feet. Each fill provides 10 minutes of foaming time.

Key Features

- 316L stainless steel, ASME rated tank and all stainless steel wetted components ensure durability and years of outstanding performance
- Designed for more controlled foaming and extended foaming time in smaller areas
- Projects a low volume of rich, clinging foam which increases chemical contact time and effectiveness
- Foaming expands the chemical and reduces over-application by providing visual assurance of coverage
- Fan pattern nozzle for quick coverage (up to 9' range)
- Adjustable foam consistency (wet/dry)
- Powered completely by compressed air
- No moving parts, virtually no maintenance required
- Available with a higher flow rate and 16 or 37.4 gallon tank (#925916, 925937)
- Available as a sprayer (#925705)
- See all Lafferty tank foamers and sprayers in [Catalog 4](#)

Includes

- All stainless steel 2-wheel cart with non-marking tires
- Stainless steel hinged mounting enclosure
- 5 gallon, 316L stainless steel, ASME rated pressure tank
- Stainless steel pressure relief pop-off valve
- Machined stainless steel foamer body
- 25' discharge hose, stainless steel discharge ball valve, polypropylene foam wand and fan nozzle

OPTIONS

Stainless Steel Hose Racks

Small Stainless Steel Hose Rack # 224145

Proportioning / Filling Options

1-Way Ball Valve Mixing Station (4 GPM) # 985100

1-Way Push Lever Mixing Station (4 GPM) # 981100

Alternate Check Valves & Seals (EPDM Standard)

Check Valve, Air, SS, 1/4" MM (Viton / Hast) # 491306

O-Ring, Viton, Tank Lid, 5, 16 & 37 Gallon, ASME # 708513

APPLICATIONS

- Food & Beverage
- Agriculture/Horticulture
- Animal Health
- Vehicle Wash
- Dairy
- Hatchery
- Hood & Vent
- Industrial
- Military
- Pharm/Bio
- And Many Other Applications!



REQUIREMENTS

Ready-to-Use Chemical Solution

Compressed Air up to 4 CFM

Hose 1/2" ID x 25'

Nozzle 40100

Lafferty
EQUIPMENT MANUFACTURING INC.

1.501.851.2820 or 1.800.999.2820

laffertyequipment.com

