

455 2-Way Fogger

MODEL # 950202

OVERVIEW

The 455 2-Way Fogger is a dry mist sprayer that uses compressed air (35 CFM @ 80 PSI) and venturi action to draw ready-to-use chemical solution from a nearby container and project it up to 35 feet in opposite directions. The adjustable output sprays mist (fog) into the air to cover exposed surfaces and penetrate hard-to-reach areas.

Key Features

- Atomizes and sprays chemical solutions using only compressed air
- Venturi action draws pre-diluted chemical from a nearby container
- Projects up to 35' in opposite directions
- Dry fog (mist) fills the air and covers exposed surfaces with chemical, including hard-to-reach areas
- 455 foggers produce drier output, without adjustments, compared to other fogger series (633, 305, etc.)
- *Optional* metering tips can further reduce chemical usage and output wetness
- Chemical resistant polypropylene construction ensures durability and years of outstanding performance
- See [Catalog 7](#) for hand held, permanently mounted and portable foggers
- Use the Lafferty [Fogger Planning Tool](#) to design the optimal fogging system for any facility

Includes

- Machined polypropylene fogger body
- (2) Metering tip holders
- 10' chemical suction tube and strainer

OPTIONS

Stainless Steel Jug Racks

1 Gallon Round/Square	# 224200
1 Gallon Round/Square Locking	# 224200-L
2 ½ Gallon (8 ½" x 10 ½")	# 224210
5 Gallon Round/Square Locking (12" x 12")	# 224214
5 Gallon Round/Square (12" x 12")	# 224215

Safe Flow Lid™ for 1 Gallon Jugs

Lid, Suction Tube, and Strainer	# 709101
---------------------------------	----------

To Control Solution Flow (Wetness of Fog)

Metering Tips-Color Coded (Set of 20)	# 443798
Metering Tips-Color Coded (10 Smallest)	# 443794

APPLICATIONS

- Sanitizers
- Insecticides
- Agriculture/Horticulture
- Animal Health
- Dairy
- Food & Beverage
- Hatchery
- Industrial
- Janitorial/Sanitization
- Metal Processing
- Odor Control
- Pharm/Bio
- Supermarkets
- And Many Other Applications!



REQUIREMENTS

Ready-to-Use Chemical Solution

Compressed Air up to 35 CFM @ 80 PSI

Minimum Air Supply Line 3/8"