# W-100 Spray-All

MODEL # 970270

## **OVERVIEW**

The W-100 Spray-All is a water-driven, high volume spray applicator for applying chemical solutions to a variety of surfaces. This venturi injection system uses standard city water pressure (35 - 125 PSI) to draw and blend chemical concentrate into the water stream. Precision metering tips are used to create an accurately diluted solution which is projected through the discharge hose and fan nozzle as a uniform "flooding" spray. With a flow rate of around 4 gallons per minute, this unit is great for spraying down large areas or objects.



- Creates a high volume, flooding spray
- Designed for spraying large surfaces and equipment
- Fan pattern nozzle for fast coverage
- Chemical resistant wetted components ensure years of outstanding performance with minimal maintenance
- Industrial-strength design holds up in tough environments
- Use it where 35-125 PSI water is available
- Available with a lower flow rate (#970250)
- See more Lafferty Spray-Alls and other chemical applicators in Catalog 1



- · Stainless steel mounting bracket
- Stainless steel inlet and discharge ball valves
- Machined polypropylene injector body
- 20 color-coded precision metering tips to set dilution ratios
- 50' discharge hose, polypropylene wand and stainless steel fan nozzle

## **OPTIONS**

### Stainless Steel Hose Racks

Large Stainless Steel Hose Rack # 224150

### Stainless Steel Jug Racks

1 Gallon Round/Square	# 224200
1 Gallon Round/Square Locking	# 224200-L
2 ½ Gallon (8 ½" x 10 ½")	# 224210
5 Gallon Round/Square Locking (12" x 12")	# 224214
5 Gallon Round/Square (12" x 12")	# 224215

# Safe Flow Lid™ for 1 Gallon Jugs

Lid, Suction Tube, and Strainer # 709101

# Alternate Check Valve - EPDM Standard

Check Valve, Chemical, PP/Viton, 1/4" # 491315

## **APPLICATIONS**

- Agriculture/Horticulture
- Animal Health
- Food & Beverage
- Industrial
- Janitorial/Sanitation
- Metal Processing
- Supermarkets
- And Many Other Applications!



## **REQUIREMENTS**

# **Chemical Concentrate**

## Water

Temperature up to 160°F
Pressure 35 to 125 PSI
Flow 4 GPM @ 40 PSI

Supply Line 3/4"

Hose 1/2" ID x 50' Nozzle 40100

Dilution Ratio Range 914:1 to 9:1 @ 40 PSI

