315 Sanitizer

MODEL # 973650

OVERVIEW

The 315 Sanitizer is a high volume venturi injection system that uses standard city water pressure (35 - 125 PSI) to draw and blend chemical concentrate into the water stream. Precision metering tips are used to create the lean ratios required for no-rinse sanitizing in food plants. The solution is then projected through the discharge hose and fan nozzle as a 4 GPM coarse spray on to any surface or object.

Key Features

- Creates a high volume, coarse spray
- Dilute concentrated sanitizers to the lean ratios required for norinse applications in food plants
- Projects a high volume flooding spray in a fan pattern for complete coverage
- Chemical resistant wetted components ensure years of outstanding performance with minimal maintenance
- Industrial-strength design holds up in tough environments
- Available with a higher flow rate for even leaner dilution ratios (#973750)
- See other Lafferty Spray-Alls and more chemical applicators in Catalog 1

Includes

- · Stainless steel mounting bracket
- Stainless steel inlet and discharge ball valves
- · Machined polypropylene injector body
- 20 color-coded metering tips to set dilution ratios
- 50' discharge hose, polypropylene wand and stainless steel fan nozzle

OPTIONS

Stainless Steel Hose Racks

Large Stainless Steel Hose Rack # 224150

Stainless Steel Jug Racks

2 ½ Gal. (8 ½" x 10 ½") # 224210 5 Gallon (12" x 12") Round/Square # 224215

Safe Flow Lid™ for 1 Gallon Jugs

Lid, Suction Tube, and Strainer # 709101

Alternate Sanitizer Check Valve - Viton Standard

Check Valve, Chemical, PP/EPDM, 1/4" # 491311

APPLICATIONS

- Food & Beverage
- Agriculture/Horticulture
- Animal Health
- Dairy
- Hatchery
- Industrial
- Janitorial/Sanitation
- Pharm/Bio
- And Many Other Applications!





REQUIREMENTS

Chemical Concentrate

Water

Temperature up to 160°F
Pressure 35 to 125 PSI
Flow 4 GPM @ 40 PSI

Supply Line 1/2"

Hose 1/2" ID x 50'

Nozzle 40100

Dilution Ratio Range 914:1 to 9:1 @ 40 PSI

