

# Drum Bung Mount Asphalt Release Spray-All

MODEL # 974600

## OVERVIEW

The Asphalt Release Spray-All Drum Bung Mount is a water-driven, drum-mounted spray applicator for applying asphalt release agents on to truck beds or tools to prevent asphalt from sticking. This venturi injection system uses standard city water pressure (35 - 125 PSI) to draw and blend chemical concentrate directly from the drum into the water stream. Precision metering tips are used to create an accurately diluted solution which is projected through the discharge hose and fan nozzle as a uniform spray. With a flow rate of around 1.3 GPM @ 40 PSI, this unit is great for spraying down any sized vehicle or equipment quickly and efficiently.

## Key Features

- Screws into the 2" drum bung, equipped with both fine and coarse threads
- Designed for diluting and spraying asphalt release agents on to truck beds and asphalt tools
- Creates a 1.3 GPM @ 40 PSI, fan pattern spray for fast and even coverage
- Chemical resistant wetted components ensure years of outstanding performance with minimal maintenance
- Use it where 35-125 PSI water is available
- Available as a wall-mounted unit (#974112)
- See other Lafferty asphalt release equipment and industrial chemical applicators in [Catalog 8](#)

## Includes

- Machined polypropylene injector body
- 20 color-coded precision metering tips to set dilution ratios
- 25' discharge hose
- All stainless steel ball valve, wand & fan nozzle

## OPTIONS

### Stainless Steel Hose Racks

Small Stainless Steel Hose Rack # 224145

### Alternate Chemical Check Valve - Viton Standard

Check Valve, Chemical, PP(W), 1/4" (EPDM) # 491401

## APPLICATIONS

- Asphalt
- Industrial



## REQUIREMENTS

### Chemical Concentrate

#### Water

Temperature	up to 160°F
Pressure	35 to 125 PSI
Flow	1.45 GPM @ 40 PSI
Supply Line	1/2"

#### Hose

1/2" ID x 25'

#### Nozzle

2540

#### Dilution Ratio Range

331:1 to 3:1 @ 40 PSI



**536500 Insulator for 1/4" SS Wand**

*Insulates hands from hot or cold extremes and provides comfortable secure grip.*