Portable 4-Wheel 5 Gallon Uni-Body™ LC Foamer

MODEL # 975805

OVERVIEW

The Portable 4-Wheel 5 Gallon Uni-Body™ LC Foamer is a medium volume foam applicator featuring an all stainless steel cart assembly. It will project foaming chemicals on to any surface up close or at distances up to 12 feet. This venturi injection system uses standard city water pressure (35 - 125 PSI) to draw and blend chemical concentrate into the water stream to create an accurately diluted solution. Rich, clinging foam is created by injecting compressed air into the solution to greatly increase volume and coverage ability. The foam is then projected through the discharge hose and fan nozzle.

Key Features

- Creates a medium volume of rich, clinging foam which increases chemical contact time and effectiveness
- Foaming expands the chemical and reduces over-application by providing visual assurance of coverage
- Fan pattern nozzle for fast coverage (up to 12' range)
- Covers up to 500 sq ft (46.5 sq m) in 2 minutes
- Adjustable foam consistency (wet/dry)
- Chemical resistant wetted components ensure years of outstanding performance with minimal maintenance
- Industrial-strength design holds up in tough environments
- Available for 2 chemicals (#975806)
- See other configurations of Lafferty city water pressure foamers in Catalog 1

Includes

- All stainless steel 4-wheel cart with non-marking tires and integrated hose rack
- Stainless steel, round, 5 gallon jug rack (square optional)
- Machined polypropylene foamer body
- 20 color-coded precision metering tips to set dilution ratios
- 25' discharge hose, stainless steel ball valve, polypropylene foam wand and fan nozzle

OPTIONS

5 Gallon Pail	
Pail, 5 Gallon Round W/ Suction Stem	# 709105
Safe Flow Lid™ for 1 Gallon Jugs	
Lid, Suction Tube, and Strainer	# 709101
Square Jug Rack Conversion	
Specify Round or Square Jug Racks at time of order	
Alternate Check Valves - EPDM Standard	
Check Valve, Chemical, PP/Viton, 1/4"	# 491315
Check Valve, Air, SS/Viton, 1/4"	# 491306

APPLICATIONS

- Agriculture/Horticulture
- Animal Health
- Vehicle Wash
- Dairy
- Food & Beverage
- Industrial
- Metal Processing
- And Many Other Applications!

REQUIREMENTS

Chemical Concentrate	
Water	
Temperature	up to 160°F
Pressure	35 to 125 PSI
Flow	1.34 GPM @ 40 PSI
Supply Line	1/2"
Compressed Air	up to 3 CFM
Hose	3/4" ID x 25'
Nozzle	50250
Dilution Ratio Range	306:1 to 6:1 @ 40 PSI

Lafferty
EQUIPMENT MANUFACTURING LLC
CFS TECHNOLOGIES
1.501.851.2820 | 1.800.999.2820
www.laffertyequipment.com