

Model 50 Compact Sprayer (No Gun)

MODEL # 969848-B32

OVERVIEW

The Model 50 Compact Sprayer is a medium volume hose-end spray applicator for diluting and applying chemicals to any surface up close or at a distance. This unit uses standard city water pressure to draw chemical concentrate from the attached bottle and blend it into the water stream. This accurately diluted solution is then projected through the recessed fan nozzle. This handy sprayer is offered without a trigger gun and can be used in conjunction with the gun on another compact unit. Use it with a Compact Foamer to easily switch between foam, rinse and spray.

Key Features

- Attaches to the gun or ball valve from another Lafferty Compact Sprayer or Foamer
- Allows the user to easily switch chemicals or to use in conjunction with a Compact Foamer to create a foam/rinse/spray cleaning system
- Accurately dilutes chemical concentrate and applies it as a medium volume spray
- Durable! Injector body is machined in the USA, not molded
- Outlasts and outperforms similar molded plastic products
- With less than half the flow rate of competing models, you save money
- Light, 32 oz bottle reduces wrist and arm fatigue as well as the risk of repetitive strain injuries
- No moving parts! Venturi action dilutes chemical consistently with precision metering tips
- Great performance with water pressure as low as 20 PSI
- Recessed fan nozzle for protection and fast coverage
- Color-coded lids help identify equipment and chemicals to enhance user safety (blue standard - red, yellow, or green optional)
- Available with a lower flow rate (#969818-B32)
- Available with a garden hose gun (#969850-B32)
- See more Lafferty compact units and other chemical applicators in [Catalog 11](#)

Includes

- Machined polypropylene injector body
- Fan nozzle with nozzle protector
- 32 oz wide-mouth, polyethylene bottle
- 20 color-coded precision metering tips to set dilution ratios
- Quick disconnect plug

OPTIONS

Additional Bottles

Bottle, 32oz (Includes Solid Lid) # 709082

Unit Storage Rack

Compact Foamer/Sprayer Rack, Stainless Steel # 224301

Quick Disconnect Socket

QD, SS, Socket FGH # 350474SS



REQUIREMENTS

Chemical Concentrate

Water

Temperature up to 160°F
Pressure 20 - 100 PSI
Flow 2.3 GPM @ 40 PSI
Supply Line 1/2"

Nozzle 2550

Dilution Ratio Range 526:1 to 5:1 @ 40 PSI

APPLICATIONS

- Agriculture/Horticulture
- Animal Health
- Vehicle Wash
- Concrete
- Dairy
- Food & Beverage
- Hatchery
- Industrial
- Janitorial/Sanitation
- Metal Processing
- Military
- Pharm/Bio
- Supermarkets
- And Many Other Applications!

Lafferty
EQUIPMENT MANUFACTURING LLC
CFS TECHNOLOGIES

1.501.851.2820 | 1.800.999.2820
www.laffertyequipment.com