

BPSSDU Foamer

MODEL # 912115DU

OVERVIEW

The BPSSDU Foamer is a medium volume foam applicator for simultaneously applying 2 foaming chemicals to any surface up close or at a distance. This venturi injection system uses boosted water pressure (125 - 350 PSI) to draw and blend 2 chemical concentrates into the water stream at the same time to create an accurately diluted solution. Rich, clinging foam is created by injecting compressed air into the solution to greatly increase volume and coverage ability. The foam is then projected through the foam hose and fan nozzle at distances up to 13 feet.

Key Features

- Simultaneously blends 2 chemicals into the water stream
- Stainless steel foamer body for maximum durability and chemical resistance
- Designed for foam cleaning medium to large surfaces
- Projects a medium volume of rich, clinging foam which increases chemical contact time and effectiveness
- Foaming expands the chemical and reduces over-application by providing visual assurance of coverage
- Fan pattern nozzle for quick coverage (up to 13' range)
- Covers up to 500 sq ft (46.5 sq m) in 1 minute
- Adjustable foam consistency (wet/dry)
- Chemical resistant wetted components ensure years of outstanding performance with minimal maintenance
- Industrial-strength design holds up in tough environments
- Available for just one chemical (#912115)
- See other configurations of Lafferty boosted water pressure foamers in [Catalog 2](#)

Includes

- Stainless steel mounting bracket
- Machined stainless steel foamer body
- 20 color-coded precision metering tips to set dilution ratios
- 50' discharge hose, polypropylene foam wand & fan nozzle

OPTIONS

Stainless Steel Hose Racks

Large Stainless Steel Hose Rack # 224150

Stainless Steel Jug Racks

Jug Rack, SS, 1 Gallon, Round/Square # 224200

Jug Rack, SS, 2 1/2 Gallon # 224210

Jug Rack, SS, 5 Gallon, Round/Square # 224215

Safe Flow Lid™ for 1 Gallon Jugs

Lid, Suction Tube, and Strainer # 709101


Alternate Check Valves - EPDM Standard

Check Valve, Chemical, PP/Viton, 1/4" # 491315

Check Valve, Air, SS/Viton, 1/4" # 491306

APPLICATIONS

- Food & Beverage
- Agriculture/Horticulture
- Animal Health
- Dairy
- Hatchery
- Industrial
- Metal Processing
- Military
- Paper Mill
- And Many Other Applications!



REQUIREMENTS

Chemical Concentrate

Water

Temperature up to 180°F
 Pressure 125 to 350 PSI
 Flow 3.0 GPM @ 250 PSI
 Supply Line 1/2"

Compressed Air

up to 4 CFM

Hose

3/4" ID x 50'

Nozzle

65300

Dilution Ratio Range

679:1 to 6:1 @ 250 PSI