

# 3-Way Ball Valve Mixing Station

MODEL # 985300

## OVERVIEW

The 3-Way Ball Valve Mixing Station is an ASSE 1055 certified chemical proportioner that accurately dilutes chemicals to the required ratios and dispenses into any size container. This venturi injection system uses city water pressure (25 - 125 PSI) to draw and blend chemical concentrate into the water stream and precision metering tips to set the dilution ratio for each valve. Ball valve activation allows for hands-free dispensing. Choose a factory-set flow rate for each ball valve at the time of order (Bottle Fill, Low Flow, High Flow).

## Key Features

- Eliminates manual mixing and optimizes chemical utilization, employee safety and labor efficiency
- Ball valve activation allows for hands-free dispensing
- Chemical resistant wetted components ensure years of outstanding performance with minimal maintenance
- Industrial-strength design holds up in tough environments
- Water pressure gauge eliminates guessing, reduces set-up time and helps with troubleshooting
- The dilution ratio for each valve is set independently
- Draws chemical concentrate from any sized container
- Choice of left or right side water inlet
- Mixing stations can be plumbed in series
- Choice of flow rates for filling small to large containers
- Please specify the flow rate for each valve when ordering
  - Bottle Fill (BF), Low Flow (LF), High Flow (HF)
- Certified to ASSE Standard 1055 for backflow prevention
- Available with push lever activation (#981300)
- See Lafferty chemical management systems in [Catalog 9](#)

## Includes

- Stainless steel mounting bracket
- Activation ball valves
- Polypropylene injector bodies
- Integrated brass hose connection vacuum breakers
- Easy-to-read water pressure gauge for accurate tip selection
- 20 color-coded metering tips for setting dilution ratios
- (3) 6' chemical suction tubes with strainers
- (3) open flow discharge tubes (4.5' for LF/HF, 1' for BF)

## OPTIONS

### Stainless Steel Jug Racks

1 Gallon Round/Square	# 224200
1 Gallon Round/Square Locking	# 224200-L
2 ½ Gallon (8 ½" x 10 ½")	# 224210
5 Gallon Round/Square Locking (12" x 12")	# 224214
5 Gallon Round/Square (12" x 12")	# 224215

### Safe Flow Lid™ for 1 Gallon Jugs

Lid, Suction Tube, and Strainer	# 709101
---------------------------------	----------

### Alternate Chemical Check Valve - EPDM Standard

Check Valve, Chemical, PP, 1/4" (Viton)	# 491402
---	----------

### Jumper Hose with GH Fittings (10')

GH Hose, Blue, 1/2" x 10'	# 804410B
---------------------------	-----------

### Red, Blue, Green & Yellow Ball Valve Handles

# 413511RED, 413511BLU, 413511GRN, 413511YLW

## APPLICATIONS

- Agriculture/Horticulture
- Animal Health
- Vehicle Wash
- Food & Beverage
- School Hygiene
- Industrial
- Janitorial/Sanitation
- Supermarkets
- And Many Other Applications!



## REQUIREMENTS

### Chemical Concentrate

#### Water

Temperature	up to 160°F
Pressure	25-125 PSI
Supply Line	1/2" Minimum

#### Flow

High Flow (Black Injector)	4.0 - 7.3 GPM
Low Flow (White Injector)	1.9 - 3.4 GPM
Bottle Fill (Blue Injector)	0.6 - 1.0 GPM

### Dilution Ratio Range @ 40 PSI

High Flow	1,031:1 to 4.8:1
Low Flow	480:1 to 3.5:1
Bottle Fill	142:1 to 1.7:1

**Lafferty**  
EQUIPMENT MANUFACTURING LLC  
CFS TECHNOLOGIES

1.501.851.2820 | 1.800.999.2820  
www.laffertyequipment.com