

37.4 Gallon Tank Solvent Sprayer

MODEL # 925737-D

OVERVIEW

The 37.4 Gallon Tank Solvent Sprayer is a chemical spray applicator with an all stainless steel cart assembly that is suitable for handling many higher-flash-point solvents, including d-limonene. Connect compressed air to pressurize the 316L stainless steel ASME rated tank and project ready-to-use solution through the hose, wand and fan pattern spray nozzle. Includes 2 spray nozzles which provide either 51 or 110 minutes of spraying time depending on the nozzle used.

Key Features

- Solvent resistant components make this unit suitable for many higher-flash-point solvents, including d-limonene
- 316L stainless steel, ASME rated tank and all stainless steel wetted components ensure durability and years of outstanding performance
- Draws pre-diluted chemical from the 37.4 gallon tank
- Alternate nozzles to project a low or medium volume fan pattern spray
- Sprays for 51 or 110 minutes per tank fill, depending on the nozzle selected
- Powered solely by compressed air
- Available with a 5 or 16 gallon tank (#925705-D, 925716-D)
- Available for non-solvents (#925737)
- See other air-operated sprayers and foamers in [Catalog 4](#)

Includes

- All stainless steel 4-wheel cart
- Non-marking tires with front, stainless steel swivel casters
- Stainless steel, hinged mounting enclosure
- 37.4 gallon, 316L stainless steel, ASME rated pressure tank
- Stainless steel pressure relief pop-off valve
- 50' solvent resistant discharge hose, stainless steel ball valve, stainless steel wand & 2 fan nozzles

OPTIONS

Proportioning / Filling Options

1-Way Ball Valve SS Mixing Station (4 GPM) # 985100SS

APPLICATIONS

- Aviation
- Industrial
- Metal Processing
- Military
- Pharm/Bio



REQUIREMENTS

Ready-to-Use Chemical Solution

Compressed Air	up to 3 CFM
Minimum Air Supply Line	3/8"
Hose	1/2" ID x 50'
Nozzle	2503 or 2506

Lafferty
EQUIPMENT MANUFACTURING INC.

1.501.851.2820 or 1.800.999.2820
laffertyequipment.com

