

# 16 Gallon Tank Solvent Sprayer

MODEL # 925716-D

## OVERVIEW

The 16 Gallon Internal Tank Solvent Sprayer is a chemical spray applicator with an all stainless steel cart assembly that is suitable for handling many higher-flash-point solvents, including d-limonene. Connect compressed air to pressurize the 316L stainless steel ASME rated tank and project ready-to-use solution through the hose, wand and fan pattern spray nozzle. Includes 2 spray nozzles which provide either 22 or 47 minutes of spraying time depending on the nozzle used.

## Key Features

- Solvent resistant components make this unit suitable for many higher-flash-point solvents, including d-limonene
- 316L stainless steel, ASME rated tank and all stainless steel wetted components ensure durability and years of outstanding performance
- Draws pre-diluted chemical from the 16 gallon tank
- Alternate nozzles to project a low or medium volume fan pattern spray
- Sprays for 22 or 47 minutes per tank fill
- Powered solely by compressed air
- Available with a 5 gallon tank (#925705-D)
- Available for non-solvents (#925716)
- See other air-operated sprayers and foamers in [Catalog 4](#)

## Includes

- All stainless steel 2-wheel cart with non-marking tires
- Stainless steel, hinged mounting enclosure
- 16 gallon, 316L stainless steel, ASME rated pressure tank
- Stainless steel pressure relief pop-off valve
- 25' solvent resistant discharge hose, stainless steel ball valve, stainless steel wand & 2 fan nozzles

## OPTIONS

### Proportioning / Filling Options

1-Way Ball Valve SS Mixing Station (4 GPM)

# 985100SS

## APPLICATIONS

- Aviation
- Industrial
- Metal Processing
- Military
- Pharm/Bio



## REQUIREMENTS

### Ready-to-Use Chemical Solution

Compressed Air up to 3 CFM

Minimum Air Supply Line 3/8"

Hose 1/2" ID x 25'

Nozzle 2503 or 2506