

High Volume 1553 Mixing Station

MODEL # 985855

OVERVIEW

The High Volume 1553 Mixing Station is a 15 GPM @ 40 PSI chemical proportioner for accurately diluting a chemical concentrate to the required ratio and for rapidly filling large containers with diluted, ready-to-use chemical solution. This venturi injection system uses standard city water pressure (35 - 125 PSI) to draw and blend chemical concentrate into the water stream to create an accurately diluted solution. Ball valve activation allows for hands-free dispensing.

Key Features

- Eliminates manual mixing and optimizes chemical utilization, employee safety and labor efficiency
- Ball valve activation allows for hands-free dispensing
- Quickly fills floor scrubbers, tank foamers/sprayers or any large container at 15 GPM @ 40 PSI to minimize downtime
- Chemical resistant wetted components ensure years of outstanding performance with minimal maintenance
- Dilution ratio controlled with precision metering tips
- Draws chemical concentrate from any sized container
- Available with a discharge trigger gun or ball valve & wand
- Available with a lower flow rate (#985845, 985835)
- See other chemical management systems in [Catalog 9](#)

Includes

- Stainless steel mounting bracket
- Stainless steel activation ball valve
- Polypropylene injector body
- 20 color-coded precision metering tips to set dilution ratios
- 10' open flow discharge hose

OPTIONS

Stainless Steel Hose Racks

Small Stainless Steel Hose Rack # 224145

Stainless Steel Jug Racks

5 Gallon Round/Square Locking (12" x 12") # 224214

5 Gallon Round/Square (12" x 12") # 224215

For Stronger Ratios or Viscous Chemicals

1/2" Chemical Pick-up Assembly (Viton) # 491404-A

1/2" Chemical Pick-up Assembly (EPDM) # 491403-A

Alternate Chemical Check Valve - Viton Standard

Check Valve, Chemical, PP(W), 1/4" (EPDM) # 491401

APPLICATIONS

- Filling Floor Scrubbers and Tank Foamers
- Agriculture/Horticulture
- Food & Beverage
- Industrial
- Janitorial/Sanitation
- Metal Processing
- Pharm/Bio
- Supermarkets
- And Many Other Applications!



REQUIREMENTS

Chemical Concentrate

Water

Temperature up to 160°F
 Pressure 35 to 125 PSI
 Flow 15 GPM @ 40 PSI
 Supply Line 3/4"

Hose

1" ID x 10'

Dilution Ratio Range @ 40 PSI

985855 3,429:1 to 14:1
 With Dual Pick-up Kit 14:1 to 7.0:1