

1-Way Acid LV Foamer

MODEL # 972306-LV

OVERVIEW

The 1-Way Acid LV Foamer is a low volume foam applicator for applying highly corrosive chemicals such as those used to remove concrete and for aluminum brightening. This acid-resistant venturi injection system uses standard city water pressure (40 - 125 PSI) to draw and blend concentrated acid into the water stream to create a highly concentrated and accurately diluted solution. A low volume of rich, clinging foam is created by injecting compressed air into the solution to greatly increase volume and coverage ability. The foam is then projected through the discharge hose, extended wand and fan nozzle at distances up to 9 feet.

Key Features

- Achieves strong concentrations up to 2.2 to 1
- Weaker dilution ratios controlled by precision metering tips
- Projects a low volume of rich, clinging foam which increases chemical contact time and effectiveness
- Foaming expands the chemical and reduces over-application by providing visual assurance of coverage
- Fan pattern nozzle for even coverage (up to 9' range)
- Adjustable foam consistency (wet/dry) with a concealed air regulator to discourage unauthorized tampering
- Corrosion resistant wetted components ensure durability and years of reliable service
- Available with a medium or high flow rate (#972306, 972326)
- See other Lafferty acid sprayers and foamers in [Catalog 8](#)

Includes

- Polypropylene mounting bracket and cover
- PVC inlet and discharge ball valves
- Machined polypropylene injector body
- 20 color-coded precision metering tips to set dilution ratios
- 40' discharge hose, polypropylene wand and fan nozzle

OPTIONS

Stainless Steel Hose Racks

Large Stainless Steel Hose Rack

224150

Stainless Steel Jug Racks

2 ½ Gal. (8 ½" x 10 ½")

224210

5 Gallon (12" x 12") Round/Square

224215

Safe Flow Lid™ for 1 Gallon Jugs

Lid, Suction Tube, and Strainer

709101

APPLICATIONS

- Concrete
- Food & Beverage
- Industrial
- Metal Processing
- Pharm/Bio
- And Many Other Applications!



REQUIREMENTS

Chemical Concentrate

Water

Temperature	up to 160°F
Pressure	40 to 125 PSI
Flow	0.65 GPM @ 40 PSI
Supply Line	1/2"

Compressed Air

up to 1.25 CFM

Hose

3/4" ID x 40'

Nozzle

40150

Dilution Ratio Range

149:1 to 2:1 @ 40 PSI