High Volume SS Mixing Station

MODEL # 985835SS

OVERVIEW

The High Volume SS Mixing Station is a 9.4 GPM @ 40 PSI chemical proportioner for accurately diluting a chemical concentrate and quickly filling large containers with ready-to-use chemical solution. This stainless steel venturi injection system uses standard city water pressure (35 - 125 PSI) to draw and blend chemical concentrate into the water stream. Ball valve activation allows for hands-free dispensing.

Key Features

- Eliminates manual mixing and optimizes chemical utilization, employee safety and labor efficiency
- Ball valve activation allows for hands-free dispensing
- Quickly fills floor scrubbers, tank foamers/sprayers or any large container at 9.4 GPM @ 40 PSI to minimize downtime
- Stainless steel injector body and chemical-resistant wetted components ensure durability and years of outstanding performance with minimal maintenance
- Dilution ratio controlled with precision metering tips
- Draws chemical concentrate from any sized container
- Optional trigger gun or ball valve & wand
- Available with a polypropylene injector body (#985835)
- See other chemical management systems in Catalog 9

Includes

- Stainless steel mounting bracket
- Stainless steel activation ball valve
- Stainless steel injector body and check valve
- 20 color-coded precision metering tips to set dilution ratios
- 10' open flow discharge hose with 1/2" MPT hose-end fitting for optional attachments

OPTIONS

Stainless Steel Hose Racks	
Small Stainless Steel Hose Rack	# 224145
Stainless Steel Jug Racks	
5 Gallon Round/Square Locking (12" x 12")	# 224214
5 Gallon Round/Square (12" x 12")	# 224215
Hose & Trigger Gun	
Hose, Blue, 3/4" x 25', 1/2" MPT	# 803725
Trigger Gun, PP-V	# 320800
Hose, Ball Valve & Wand	
Hose, Blue, 3/4" x 25', 1/2" MPT	# 803725
Ball Valve, SS, 1/2" FM	# 413641RH
Wand, PP	# 536603
Alternate Check Valve - EPDM Standard	
Check Valve, Chemical, SS, Viton, 1/4"	# 491324-V
Check Valve, Chemical, SS, Kalrez, 1/4"	# 491324-K

REQUIREMENTS

Chemical Concentrate	
Water	
Temperature	up to 180°F
Pressure	35 to 125 PSI
Flow	9.40 GPM @ 40 PSI
Supply Line	3/4"
Hose	3/4" ID x 10'
Nozzle	None - Open Flow
Dilution Ratio Range	2,149:1 to 15:1 @ 40 PSI

APPLICATIONS

- Filling Floor Scrubbers and Tank Foamers
- Agriculture/Horticulture
- Food & Beverage
- Industrial
- Janitorial/Sanitation
- Metal Processing
- Pharm/Bio
- Supermarkets
- And Many Other Applications!

Lafferty EQUIPMENT MANUFACTURING LLC
CFS TECHNOLOGIES
1.501.851.2820 | 1.800.999.2820
www.laffertyequipment.com