

Drum Bung Mount Uni-Body™ W-50 Spray All

MODEL # 975050DBM

OVERVIEW

The Drum Bung Mount Uni-Body™ W-50 Spray-All has threads to fit most bung openings, and is a water-driven, medium volume sprayer that mixes chemical with water and projects the solution in a uniform fan pattern. This venturi injection system uses standard city water pressure (35 - 125 PSI) to draw chemical concentrate directly from the drum into the water stream. Precision metering tips control chemical volume to create an accurately diluted solution that is projected through the discharge hose and fan nozzle. With a flow rate of around 2 gallons per minute, this unit is great for spraying virtually any size area or object quickly and efficiently.

Key Features

- Screws into, and dispenses directly from, chemical concentrate drums for increased efficiency
- Equipped with both fine and coarse threads
- Creates a medium volume, heavy spray
- Designed for spraying medium to large surfaces and objects
- Fan pattern nozzle for even coverage
- Chemical resistant wetted components ensure years of outstanding performance with minimal maintenance
- Use it anywhere 35-125 PSI water is available
- Alternate configuration discourages unauthorized changes to the dilution ratio by restricting metering tip access
- Available as a wall-mounted unit (#975050)
- See other Lafferty Spray-Alls and more chemical applicators in [Catalog 1](#)

Includes

- Machined polypropylene drum bung injector body
- 20 color-coded metering tips for setting dilution ratios
- 50' discharge hose, stainless steel discharge ball valve, polypropylene wand and stainless steel fan nozzle

OPTIONS

Stainless Steel Hose Racks

Large Stainless Steel Hose Rack # 224150

Alternate Check Valve - EPDM Standard

Check Valve, Chemical, PP/Viton, 1/4" # 491315

APPLICATIONS

- Agriculture/Horticulture
- Animal Health
- Food & Beverage
- Industrial
- Janitorial/Sanitation
- Metal Processing
- Supermarkets
- And Many Other Applications!



REQUIREMENTS

Chemical Concentrate

Water

Temperature	up to 160°F
Pressure	35 to 125 PSI
Flow	2.3 GPM @ 40 PSI
Supply Line	1/2"

Hose

1/2" ID x 50'

Nozzle

2550

Dilution Ratio Range

526:1 to 7:1 @ 40 PSI