

Drum Bung Mount Uni-Body™ A-25 Airless Foamer

MODEL # 975075DBM

OVERVIEW

The Drum Bung Mount Uni-Body™ A-25 Airless Foamer has threads to fit most bung openings, and is a medium volume foam generator that mixes chemical with water and projects a wet, foamy solution on to any surface up close or at distances up to 6 feet. This venturi injection system uses standard city water pressure (35 - 125 PSI) to draw chemical concentrate directly from the drum into the water stream. Precision metering tips control chemical volume to create an accurately diluted solution that is projected through the discharge hose and the "airless" foam wand, which draws in atmospheric air to create wet, clinging foam, without compressed air.

Key Features

- Screws into, and dispenses directly from, chemical concentrate drums for increased efficiency
- Equipped with both fine and coarse threads
- Creates a high volume, flooding spray
- Designed for spraying large surfaces and objects
- Fan pattern nozzle for even coverage
- Chemical resistant wetted components ensure years of outstanding performance with minimal maintenance
- Use it where 35-125 PSI water is available
- Alternate configuration discourages unauthorized changes to the dilution ratio by restricting metering tip access
- Available as a wall-mounted unit (#975070)
- See other Lafferty Spray-Alls and more chemical applicators in [Catalog 1](#)

Includes

- Machined polypropylene drum bung injector body
- 20 color-coded metering tips for setting dilution ratios
- 50' discharge hose, stainless steel discharge ball valve, polypropylene wand and stainless steel fan nozzle

OPTIONS

Stainless Steel Hose Racks

Large Stainless Steel Hose Rack # 224150

Stainless Steel Airless Foam Wand

Wand, SS, Airless Foam, A-25SS # 536625SS

Alternate Check Valve - EPDM Standard

Check Valve, Chemical, PP/Viton, 1/4" # 491315

APPLICATIONS

- Agriculture/Horticulture
- Animal Health
- Dairy
- Hatchery
- Industrial
- Janitorial/Sanitation
- Pharm/Bio
- Supermarkets
- And Many Other Applications!



REQUIREMENTS

Chemical Concentrate

Water

Temperature up to 160°F
 Pressure 35 to 125 PSI
 Flow 1.34 GPM @ 40 PSI
 Supply Line 1/2"

Hose

1/2" ID x 50'

Nozzle

A-25 Airless Foam Wand

Dilution Ratio Range

306:1 to 6:1 @ 40 PSI