

Drum Bung Mount Uni-Body™ A-50 Airless Foamer

MODEL # 975085DBM

OVERVIEW

The Drum Bung Mount Uni-Body™ A-50 Airless Foamer has threads to fit most bung openings, and is a medium volume foam generator that mixes chemical with water and projects a wet, foamy solution on to any surface up close or at distances up to 8 feet. This venturi injection system uses standard city water pressure (35 - 125 PSI) to draw chemical concentrate directly from the drum into the water stream. Precision metering tips control chemical volume to create an accurately diluted solution that is projected through the discharge hose and the "airless" foam wand, which draws in atmospheric air to create wet, clinging foam, without compressed air.

Key Features

- No compressed air required
- Screws into, and dispenses directly from, chemical concentrate drums for increased efficiency
- Equipped with both fine and coarse threads
- Designed for foam cleaning medium to large areas
- Projects a medium volume of wet, clinging foam which increases chemical contact time and effectiveness
- Foaming expands the chemical and reduces over-application by providing visual assurance of coverage
- Projects foam up to 8' (depending on water pressure)
- Chemical resistant wetted components ensure years of outstanding performance with minimal maintenance
- Use it where 35-125 PSI water is available
- Available with a lower flow rate (#975075)
- See other configurations of Lafferty city water pressure foamers in [Catalog 1](#)

Includes

- Machined polypropylene injector body
- 20 color-coded precision metering tips to set dilution ratios
- 50' foam hose, stainless steel discharge ball valve, machined polypropylene airless foam wand

OPTIONS

Stainless Steel Hose Racks

Large Stainless Steel Hose Rack # 224150

Stainless Steel Airless Foam Wand

Wand, SS, Airless Foam, A-50SS # 536650SS

Alternate Check Valve - EPDM Standard

Check Valve, Chemical, PP/Viton, 1/4" # 491315



REQUIREMENTS

Chemical Concentrate

Water

Temperature	up to 160°F
Pressure	35 to 125 PSI
Flow	2.3 GPM @ 40 PSI
Supply Line	1/2"

Hose

1/2" ID x 50'

Nozzle

A-50 Airless Foam Wand

Dilution Ratio Range

526:1 to 8:1 @ 40 PSI

APPLICATIONS

- Agriculture/Horticulture
- Animal Health
- Dairy
- Hatchery
- Industrial
- Janitorial/Sanitation
- Pharm/Bio
- Supermarkets
- And Many Other Applications!

