

MODEL # 918115-LB

OVERVIEW

The Lock Box HPSS Foamer is a 2 GPM @ 700 PSI foam applicator for projecting foaming chemicals on to any surface up close or at a distance. This model features a stainless steel, locking enclosure. The stainless steel venturi injection system uses high water pressure (400 - 1000 PSI) to draw and blend chemical concentrate into the water stream to create an accurately diluted solution. Rich, clinging foam is created by injecting compressed air into the solution to greatly increase volume and coverage ability. The foam is then projected through the discharge hose and fan nozzle at distances up to 13 feet.



- Stainless steel foamer body for durability and maximum chemical resistance
- Projects rich, clinging foam which increases chemical contact time and effectiveness
- Foaming expands the chemical and reduces over-application by providing visual assurance of coverage
- Fan pattern nozzle for quick coverage (up to 13' range)
- Covers up to 500 sq ft (46.5 sq m) in 2 minutes
- · Optional zero degree nozzle for increased foam throw
- Adjustable foam consistency (wet/dry)
- Stainless steel enclosure protects equipment from heavy-abuse and prevents unauthorized tampering of dilution and air settings
- · Chemical resistant wetted components ensure years of outstanding performance with minimal maintenance
- Available without enclosure (#918115)
- See other Lafferty high water pressure chemical applicators in Catalog 3

Includes

- Stainless steel, locking enclosure
- Machined stainless steel foamer body
- 20 color-coded precision metering tips to set dilution ratios
- 50' discharge hose with polypropylene open flow foam wand and fan nozzle

OPTIONS

Stainless Steel Hose Racks

Large Stainless Steel Hose Rack # 224150

Stainless Steel Jug Racks

Jug Rack, SS, 1 Gallon, Round/Square # 224200 Jug Rack, SS, 2 1/2 Gallon # 224210 Jug Rack, SS, 5 Gallon, Round/Square # 224215

Safe Flow Lid™ for 1 Gallon Jugs

Lid. Suction Tube, and Strainer #709101

Optional Zero Degree Foam Nozzle (For Increased Range)

Nozzle, NPB, 1/2" - 00200 # 180144

Alternate Check Valves - EPDM Standard

Check Valve, Chemical, SS, Viton, 1/4" # 491324-V Check Valve, Air, SS, 1/4" MM (Viton / Hast) # 491306

REQUIREMENTS

Chemical Concentrate

Water

Nozzle

Temperature up to 180°F Pressure 400 to 1000 PSI 2.0 GPM @ 700 PSI Flow

Supply Line

Compressed Air up to 5 CFM Hose 1/2" ID x 50' 50250

Dilution Ratio Range 454:1 to 6:1 @ 700 PSI

APPLICATIONS

- Food & Beverage
- Animal Health
- Vehicle Wash
- Industrial
- Pharm/Bio
- And Many Other Applications!



