

Static Water Tank Level Master™ (No Tank)

MODEL # 989330

OVERVIEW

The Static Water Tank Level Master™ (No Tank) automatically maintains a constant supply of water in a paired tank (sold separately). When the water in the tank drops below a pre-set level, it is replenished using city water pressure (up to 125 PSI) and cycles continuously.

Key Features

- Automatically maintains a pre-set level of water in a paired tank (sold separately, see options)
- Ideal for locations with low or fluctuating water pressure
- Ensures on-demand water availability for use with water pumping and chemical dilution equipment
- Water flow rate of 7 GPM @ 40 PSI - fills slower with lower water pressure (ex. 5 GPM @ 20 PSI)
- Unsinkable solid polypropylene float suspended by a rigid "push rod" ensures smooth operation and prevents the float valve from sticking in the open position
- Chemical resistant wetted components ensure years of outstanding performance with minimal maintenance
- Industrial-strength design holds up in tough environments
- Paired tanks are available in several sizes and include a rigid suction tube and hose barb(s) to facilitate dispensing
- Available to dilute chemical on demand (#989303)
- See all of our Level Master™ configurations and other Lafferty chemical management systems in [Catalog 9](#)

Includes

- Water supply inlet screen
- Water supply shut-off ball valve
- Machined polypropylene body
- Magnetic float valve with solid polypropylene float suspended by rigid CPVC push rod
- Lid for a paired tank (tank not included)

OPTIONS

Level Master Tank Sizes (Specify When Ordering)

7 Gallon	# 709170
16 Gallon	# 709171
20 Gallon	# 709172



REQUIREMENTS

Paired Level Master Tank	See Options
Water Supply	Up to 7 GPM @ 40 PSI
Water Pressure	125 PSI Max.

APPLICATIONS

- Agriculture/Horticulture
- Animal Health
- Dairy
- Food & Beverage
- Hatchery
- Industrial
- Pharm/Bio
- And Many Other Applications!