

Timed Air Pump MV Entryway Foam Sanitizer

MODEL # 976125

OVERVIEW

The Timed Air Pump MV Entryway Foam Sanitizer is an automated foam applicator for projecting sanitizing chemicals on to floors of 6' wide double doors to prevent cross contamination. This system uses water pressure (20 - 60 PSI) to fill a small float tank. An air operated pump delivers the water at the appropriate pressure to a venturi injector which draws and blends chemical concentrate into the water stream to create an accurately diluted solution. Rich, clinging foam is created by injecting compressed air into the solution to greatly increase volume and coverage ability. Foam is then projected through the discharge hose and SpreaderTM nozzle. The system timer is user-programmable to meet the needs of any facility.



- Applies a layer of rich, clinging foam to entryway floors to prevent cross-contamination
- Designed for 6' wide double doors
- A cost-effective Flojet AODD pump draws water from an internal float tank to create the water pressure needed to drive the venturi injector
- Draws chemical concentrate from any nearby container
- The unique MV Spreader[™] nozzle lays a foam pattern 6' across and 6' wide to ensure all foot traffic and cart wheels are fully exposed to the sanitizer
- Automatic activation and shutoff for use in moderate to high traffic areas
- Adjustable timer controls the application of foam at regular intervals - up to 1 minute foaming and up to 1 hour off
- Adjustable foam consistency (wet/dry)
- Chemical resistant wetted components ensure durability and years of reliable service with minimal maintenance
- See Catalog 6 for other entryway configurations

Includes

- NEMA rated control box with run/delay timer
- Stainless steel enclosure
- 1/4" Flojet AODD pump (Santoprene diaphragms)
- Internal water float tank
- Machined polypropylene foamer body
- 20 color-coded precision metering tips to set dilution ratios
- Foam enhancer
- 10' discharge hose
- \bullet MV Entryway Spreader $^{\text{\tiny TM}}$ nozzle

OPTIONS

Stainless Steel Jug Racks

‡ 224200
24200-L
[‡] 224210
‡ 224214
[‡] 224215
,

Drum & Tote Stick Lengths & Seal Materials

Drum Stick, 33" (Viton or EPDM)	# 491643 / 491643-E
Drum Stick, 48" (Viton or EPDM)	# 491648 / 491648-E
Drum Stick, 54" (Viton or EPDM)	# 491645 / 491645-E
Tote Stick, 33" (Viton or EPDM)	# 491653 / 491653-E
Tote Stick, 48" (Viton or EPDM)	# 491654 / 491654-E
Tote Stick, 54" (Viton or EPDM)	# 491656 / 491656-E

Compressed Air Parp Electric 120 VAC Water 20 to 60 psi MELPFIE. HINT: Try to Eirnit the number discharge planning run.

REQUIREMENTS

Chemical Concentrate

Temperature Pressure	up to 160°F 20 to 60 PSI
Compressed Air	up to 7 CFM
Hose	1" ID x 10'

Nozzle MV Entryway Spreader

Electric 120V

Dilution Ratio Range 686:1 to 6:1 @ 60 PSI

APPLICATIONS

- Agriculture/Horticulture
- Animal Health
- Dairy
- Food & Beverage
- Hatchery
- Pharm/Bio
- And Many Other Applications!

