









2-Way Ball Valve Mixing Station (Bottle Fill, High Flow)

MODEL # VC-1065

OVERVIEW

The 2-Way Ball Valve Mixing Station is a chemical proportioner for accurately diluting 2 chemical concentrates to required ratios and filling any sized container with diluted, ready-to-use chemical solutions. This venturi injection system uses city water pressure (25 - 125 PSI) to draw and blend chemical concentrate into the water stream to create an accurately diluted solution. Ball valve activation allows for hands-free dispensing. Available with separate flow rates for each ball valve to dispense into any sized container or equipment.

Key Features

- Eliminates manual mixing and optimizes chemical utilization, employee safety and labor efficiency
- · Ball valve activation allows for hands-free dispensing
- Chemical resistant wetted components ensure years of outstanding performance with minimal maintenance
- Industrial-strength design holds up in tough environments
- The dilution ratio for each valve is set independently
- Water pressure gauge eliminates guessing, reduces set-up time and helps with troubleshooting
- · Draws chemical concentrate from any sized container
- Water inlet and gauge can be revered for alternate-side water inlet
- Mixing stations can be plumbed in series
- Bottle fill valve for filling handheld spray bottles and small containers
- High flow valve for filling larger containers

Includes

- Stainless steel mounting bracket
- Activation ball valves
- Polypropylene injector bodies
- Integrated brass back-flow preventer
- Easy-to-read water pressure gauge for accurate tip selection
- 20 color-coded metering tips for setting dilution ratios
- (2) 6' chemical suction tubes with strainers
- (2) 4.5' open flow discharge tubes

OPTIONS

Stainless Steel Jug Racks

1 Gallon Round/Square	# 224200
1 Gallon Round/Square Locking	# 224200-L
2 ½ Gallon (8 ½" x 10 ½")	# 224210
5 Gallon Round/Square Locking (12" x 12")	# 224214
5 Gallon Round/Square (12" x 12")	# 224215

Safe Flow Lid™ for 1 Gallon Jugs

Lid, Suction Tube, and Strainer # 709101

Alternate Chemical Check Valve - EPDM Standard

Check Valve, Chemical, PP, 1/4" (Viton) # 491402

Lafferty Interest additional to the base Service of the base of

REQUIREMENTS

Chemical Concentrate

Water

remperature	ub to 100.E
Pressure	25-125 PSI
Supply Line	1/2" Minimum

.... to 1000E

Flow

High Flow (Black Injector) 4.0 - 7.3 GPM Low Flow (White Injector) 1.9 - 3.4 GPM Bottle Fill (Blue Injector) 0.6 - 1.0 GPM

Dilution Ratio Range @ 40 PSI

High Flow 1,031:1 to 4.8:1 Low Flow 480:1 to 3.5:1 Bottle Fill 142:1 to 1.7:1

APPLICATIONS

- Agriculture/Horticulture
- Animal Health
- Dairy
- Food & Beverage
- Hatchery
- Janitorial/Sanitation
- And Many Other Applications!

