

Model 25 Compact Airless Foamer (Kit, Blue)

MODEL # VC-1000

OVERVIEW

The Model 25 Compact Airless Foamer is a unique medium volume hose-end foam gun for diluting and applying foaming chemicals to any surface. This unit uses standard city water pressure to draw chemical concentrate from the attached bottle and blend it into the water stream. The accurately diluted solution flows through the foam wand to create a clinging, wet foam which is then projected on to any surface up close or at distances up to 12 feet. Quick disconnect the chemical assembly to rinse.



- Creates rich, wet foam which increases chemical contact time and effectiveness.
- Foam provides visual confirmation of complete coverage
- Projects foam up to 12' (depending on water pressure)
- Slip-on Spreader Nozzle[™] allows for more efficient coverage when foaming at close-range
- Durable! Foamer body is machined in the USA, not molded
- Outlasts and outperforms similar molded plastic products
- The stainless steel quick disconnect socket features 6 retaining balls to lock the bottle and foam assembly securely in place
- Quick disconnect the foam assembly to rinse
- With less than half the flow rate of competing models, you save money
- Light, 32 oz bottle reduces wrist and arm fatigue and the risk of repetitive strain injuries
- No moving parts! Venturi action dilutes chemical consistently
- Great performance with water pressure as low as 20 PSI
- Available with heavy-duty stainless steel ball valve activation

Includes

- Machined polypropylene foamer body
- Quick disconnect plug and 6-ball socket
- 32 oz wide-mouth, polyethylene bottle with blue lid
- 20 color-coded metering tips for setting dilution ratios
- Blue garden hose gun with inlet screen/filter
- Stainless steel storage rack
- Spreader Nozzle™

OPTIONS

Stainless Steel Hose Racks

Large Stainless Steel Hose Rack # 224150 Small Stainless Steel Hose Rack # 224145

Additional Bottles

Bottle, 32oz (Includes Solid Lid) # 709082



REQUIREMENTS

Chemical Concentrate

Water

 Temperature
 up to 160°F

 Pressure
 20 - 100 PSI

 Flow
 1.25 GPM @ 40 PSI

Supply Line 1/2"

Dilution Ratio Range 286:1 to 6:1 @ 40 PSI

APPLICATIONS

- Food & Beverage
- Agriculture/Horticulture
- Animal Health
- Vehicle Wash
- Dairy
- Food & Beverage
- Hatchery
- HatcheryIndustrial
- Janitorial/Sanitation
- Pharm/Bio
- Supermarkets
- · And Many Other Applications!



