Pail/Jug Mount Uni-Body™ W-20 Spray-All

MODEL # 975018

OVERVIEW

The Pail/Jug Mount Uni-Body W-20 Spray-All is a convenient container-mounted, low-volume spray applicator. This venturi injection system uses standard city water pressure (35 - 125 PSI) to draw chemical concentrate directly from the container and blend it into the water stream. Precision metering tips create an accurately diluted solution which is projected through the discharge hose and fan nozzle as a light, uniform spray. With a flow rate of just under 1 gallon per minute, this unit is great for spraying virtually any size area or object, slowly and completely, with very little run-off.



- Screws onto, and dispenses directly from, chemical concentrate containers for increased efficiency
- Creates a low volume spray (under 1 GPM @ 40 PSI)
- Ideal for precision application in small areas and near sensitive equipment where minimal over-spray is crucial
- Fan pattern nozzle for even coverage
- Chemical resistant wetted components ensure outstanding performance with minimal maintenance - machined, not molded!
- Use it anywhere 35-125 PSI water is available
- Easy to set up no tools or mounting hardware required
- Fits 1-gallon jugs, pull-up spouts on 5-gallon pails, or any container with 38mm OD threads
- Available for coarse/fine drum bung threads (#975020DBM)
- Available as a wall-mounted unit (#975020)
- See Lafferty Spray-Alls and other chemical applicators in Catalog 11



- Water inlet ball valve
- Machined polypropylene injector body
- 18" chemical suction tube with strainer
- 20 color-coded metering tips for setting dilution ratios
- 25' discharge hose with ball valve, polypropylene wand, and stainless steel fan nozzle

OPTIONS

Stainless Steel Hose Racks

Large Stainless Steel Hose Rack # 224150 Small Stainless Steel Hose Rack # 224145

Stainless Steel Pail/Jug Racks

Jug Rack, SS, 1 Gallon, Round/Square# 224200Jug Rack, SS, 1 Gallon/5 Liter, Rectangular "F-Style"# 224201Jug Rack, SS, 5 Gallon, Round/Square# 224215Jug Stand, SS, 5 Gallon Round/Square# 224414

Alternate Check Valve - EPDM Standard

Check Valve, Chemical, PP/Viton, 1/4" # 491315

APPLICATIONS

- Agriculture/Horticulture
- Animal Health
- Vehicle Wash
- Dairy
- Food & Beverage
- Hatchery
- Industrial
- Janitorial/Sanitation
- Supermarkets
- And Many Other Applications!



REQUIREMENTS

Chemical Concentrate

Water

 Temperature
 up to 160°F

 Pressure
 35 to 125 PSI

 Flow
 0.84 GPM @ 40 PSI

Supply Line 1/2"

Hose 1/2" ID x 25'

Nozzle 2520

Dilution Ratio Range 192:1 to 6:1 @ 40 PSI













