

# 2-Way Hyper SS Foamer

MODEL # 917117

## OVERVIEW

The 2-Way Hyper SS Foamer is a 3.3 GPM @ 700 PSI foam applicator for quickly projecting 2 foaming chemicals on to any surface up close or at a distance. This stainless steel venturi injection system uses high water pressure (400 - 1000 PSI) to draw and blend chemical concentrates into the water stream to create an accurately diluted solution. Rich, clinging foam is created by injecting compressed air into the solution to greatly increase volume and coverage ability. The foam is then projected through the foam hose, wand and fan nozzle at distances up to 13 feet. Adjust the ball valves to apply the 2 chemicals separately or together.

## Key Features

- Stainless steel foamer body for maximum durability and chemical resistance
- Designed to apply 2 separate chemicals or 2 different concentrations of the same chemical
- Chemicals can be applied separately or simultaneously by adjusting the ball valves
- Projects a substantial volume of rich, clinging foam which increases chemical contact time and effectiveness
- Foaming expands the chemical and reduces over-application by providing visual assurance of coverage
- Fan pattern nozzle for quick coverage (up to 13' range)
- Covers up to 500 sq ft (46.5 sq m) in 1.5 minutes
- Optional zero degree nozzle for increased foam throw
- Adjustable foam consistency (wet/dry)
- Chemical resistant wetted components ensure years of outstanding performance with minimal maintenance
- Industrial-strength design holds up in tough environments
- Available for only 1 chemical (#917115)
- See other high water pressure applicators in [Catalog 3](#)

## Includes

- Stainless steel mounting bracket
- Machined polypropylene foamer body
- Chemical ball valves
- 20 color-coded precision metering tips to set dilution ratios
- 50' discharge hose with polypropylene open flow foam wand and fan nozzle

## OPTIONS

### Stainless Steel Hose Racks

Large Stainless Steel Hose Rack # 224150

### Stainless Steel Jug Racks

1 Gallon Round/Square # 224200

1 Gallon Round/Square Locking # 224200-L

2 ½ Gallon (8 ½" x 10 ½") # 224210

5 Gallon Round/Square Locking (12" x 12") # 224214

5 Gallon Round/Square (12" x 12") # 224215

### Safe Flow Lid™ for 1 Gallon Jugs

Lid, Suction Tube, and Strainer # 709101

### Optional Zero Degree Nozzle (For Increased Range)

Nozzle, NPB, 3/4" - 00400 # 180154

### Alternate Check Valves - EPDM Standard

Check Valve, Chemical, PP/Viton, 1/4" # 491315

Check Valve, Air, SS/Viton, 1/4" # 491306

## APPLICATIONS

- Food & Beverage
- Animal Health
- Vehicle Wash
- Industrial
- Metal Processing
- And Many Other Applications!



## REQUIREMENTS

### Chemical Concentrate

#### Water

Temperature up to 180°F  
 Pressure 400 to 1000 PSI  
 Flow 3.3 GPM @ 700 PSI  
 Supply Line 3/8"

#### Compressed Air

up to 5 CFM

#### Hose

3/4" ID x 50'

#### Nozzle

65300

#### Dilution Ratio Range

756:1 to 8:1 @ 700 PSI

**Lafferty**  
EQUIPMENT MANUFACTURING INC.

1.501.851.2820 or 1.800.999.2820

[laffertyequipment.com](http://laffertyequipment.com)