

Timed FPV-PD Asphalt Release Sprayer

MODEL # 974321-TD

OVERVIEW

The Timed FPV-PD Asphalt Release Sprayer is a chemical spray applicator for projecting ready-to-use asphalt release chemicals on to truck beds or tools to prevent asphalt from sticking. This unit features an adjustable dual-function 110V timer which controls the length of application and the delay time, which keeps the driver from immediately restarting the system. When the activation button is pressed, a Flojet air-operated, double-diaphragm pump draws pre-diluted chemical solution from a static tank and projects it through the discharge hose, trigger gun, wand and fan nozzle.

Key Features

- Projects asphalt release chemicals on to truck beds and asphalt tools as a spray
- The Flojet AODD pump draws ready-to-use chemical from a static tank
- The push button activated, adjustable, single-shot timer will apply chemical for up to 6 minutes and then delay for up to 6 minutes to prevent over-application and waste
- Fan pattern spray for fast, efficient application
- Chemical resistant wetted components ensure years of outstanding performance with minimal maintenance
- Available to dilute chemical "on-the-fly" (#977002)
- See other industrial chemical applicators in [Catalog 8](#)

Includes

- Lockable, stainless steel pump enclosure
- Control box with run & delay timers
- Remote push button activator
- 1/4" Flojet AODD pump (Viton diaphragms)
- 25' foam hose with trigger gun
- Stainless steel extension wand & fan nozzle

OPTIONS

Stainless Steel Hose Racks

Small Stainless Steel Hose Rack # 224145

Drum & Tote Stick Lengths & Seal Materials

| | |
|---------------------------------|---------------------|
| Drum Stick, 33" (Viton or EPDM) | # 491643 / 491643-E |
| Drum Stick, 48" (Viton or EPDM) | # 491648 / 491648-E |
| Drum Stick, 54" (Viton or EPDM) | # 491645 / 491645-E |
| Tote Stick, 33" (Viton or EPDM) | # 491653 / 491653-E |
| Tote Stick, 48" (Viton or EPDM) | # 491654 / 491654-E |
| Tote Stick, 54" (Viton or EPDM) | # 491656 / 491656-E |

APPLICATIONS

- Asphalt



REQUIREMENTS

Ready-to-Use Chemical Solution

| | |
|----------------|---------------|
| Compressed Air | up to 4 CFM |
| Hose | 1/2" ID x 25' |
| Nozzle | 2520 |
| Electric | 120V |