RADAR[™] EP-LM Spray System With Enclosed 7 Gallon Level Master[™] And Heaters

MODEL # 977892

OVERVIEW

The *RADAR*[™] EP-LM Spray System with Enclosed Level Master[™] and Heaters is an electric eye activated asphalt release applicator that mounts to a user-supplied drive-though arch for spraying asphalt truck beds. This system uses an electric pump to draw ready-to-use chemical solution from the included 7 Gallon Level Master[™] tank which maintains a constant supply of solution. When a truck breaks the electric eye's line-of-sight, a delay timer allows the driver to position the truck under the spray nozzle before spraying begins and a run timer applies release agent for a pre-set amount of time or until the vehicle leaves the spraying area, whichever occurs first. This all-weather unit features a heated enclosure for both the pump and Level Master[™].

Key Features

- Designed to spray asphalt release chemicals on to truck beds from a nozzle that attaches to an existing drive-through spray bar
- The electric pump draws ready-to-use chemical solution from the 7 Gallon Level Master[™] which automatically maintains a constant supply of solution
- The Level Master[™] and pump are housed in heated enclosures for use in colder conditions
- The system delays for an adjustable length of time when a truck breaks the beam of the electric eye, allowing the driver to position the truck, before activating for an adjustable, pre-set length of time
- The driver remains in his cab and avoids the risk of slip-and-fall injury and chemical waste
- Evenly coats the truck bed in just seconds, reducing run-off and chemical waste
- Spraying will stop if the driver leaves the area early
- The Level Master™ achieves a wide range of dilution ratios using city water pressure and precision metering tips
- Chemical resistant wetted components ensure years of outstanding performance with minimal maintenance
- See other Lafferty asphalt release equipment and industrial chemical applicators in Catalog 8


Includes

- 2 heated, lockable, stainless steel enclosures
- 110V Electric Pump
- Control box with delay/run timers and electric eye set
- 7 Gallon Level Master™ system
- 40' discharge hose with custom fan spray nozzle

OPTIONS

Drum & Tote Stick Lengths & Seal Materials

Drum Stick, 33" (Viton or EPDM) Drum Stick, 48" (Viton or EPDM) Drum Stick, 54" (Viton or EPDM) Tote Stick, 33" (Viton or EPDM) Tote Stick, 48" (Viton or EPDM) Tote Stick, 54" (Viton or EPDM) # 491643 / 491643-E # 491648 / 491648-E # 491645 / 491645-E # 491653 / 491653-E # 491654 / 491654-E # 491656 / 491656-E





REQUIREMENTS

Chemical Concentrate

Water	
Temperature	up to 160°F
Pressure	35 to 125 PSI
Supply Line	1/2"
Hose	3/4" ID x 40'
Nozzle	#180193SS
Electric	120V / 20A

See Separate Instructions for:

Level Master™ (Single 989303 Float)

APPLICATIONS

Asphalt



Asphalt Release Spray Nozzle Assembly

Provides a coarse, wide fan spray pattern for quick, complete coverage.





1.501.851.2820 | 1.800.999.2820 www.laffertyequipment.com