

2-Hose Low Volume Foam-All

MODEL # BLU37

OVERVIEW

The Blue Mule 2-Hose Low Volume Foam-All is a combination applicator for applying one or two chemical products as wet, clinging foam. This venturi injection system uses city water pressure (35 - 125 PSI) to draw and blend chemical concentrates into the water streams to create accurately diluted solutions. Precision metering tips are used to control chemical usage independently for each hose. The mixed solutions flows through the hoses to the "airless" foam wands which draw in atmospheric air to create and project foam in a fan pattern or narrow stream. Hoses can be used independently or simultaneously.

Key Features

- Projects a low volume of wet, clinging, foamy lather
 - Foam increases chemical contact time and effectiveness
 - Low volume foam doesn't run wastefully to the ground
 - Foaming expands the chemical and reduces over-application by providing visual assurance of coverage
- Dilutes chemical products on-demand
 - Product is mixed as it is needed, ensuring optimal chemical efficiency
 - No need to spend valuable time pre-mixing products
 - Set the dilution ratio for each hose independently
 - Works with any brand of chemical products
- Requires less than 1 GPM at 40 PSI water pressure to operate both hoses simultaneously (even less for just one hose)
 - Conserves water and chemical
- The unique uni-body design is both compact and cost-effective
- Lightweight foam nozzles reduce wrist strain
- Adjustable fan pattern nozzle for wide coverage or longer foam throw
- Low maintenance over years of reliable service
 - Machined, not molded, polypropylene components
 - Industrial strength metal fittings
 - Each component can be serviced or replaced individually (should the need arise)

Includes

- Garden hose inlet adapter
- Machined polypropylene injector body
- (2) Hose activation ball valves
- (2) 10 color-coded precision metering tips to set dilution ratios
- (2) 10' discharge hoses with machined polypropylene airless foam wands

OPTIONS

Stainless Steel Hose Racks

Small Stainless Steel Hose Rack # 224145

Stainless Steel Jug Racks

1 Gallon Round/Square # 224200

1 Gallon Round/Square Locking # 224200-L

Safe Flow Lid™ for 1 Gallon Jugs

Lid, Suction Tube, and Strainer # 709101

Alternate Check Valve - EPDM Standard

Check Valve, Chemical, PP/Viton, 1/4" # 491315



REQUIREMENTS

Chemical Concentrate

Water

Temperature up to 160°F
 Pressure 50 to 125 PSI
 Flow 0.8 GPM @ 40 PSI
 Supply Line 1/2"

Hose

3/8" ID x 10'

Nozzle

#10 Bullet (x2 Hoses)

Dilution Ratio Range

183:1 to 4:1 @ 40 PSI

APPLICATIONS

- Pet Bathing
- Agriculture/Horticulture
- Animal Health
- Vehicle Wash
- Industrial
- Any Low Volume Foaming!