

Portable 2 Wheeled 20 Gallon Liberty Foamer

MODEL # 941219

OVERVIEW

The Portable 2-Wheel 20 Gallon Liberty Foamer is a medium volume foam applicator for projecting foaming chemicals on to any surface up close or at distances up to 10 feet. This unit features an all stainless steel 2-wheel cart and enclosure and uses a cost-effective Flojet air-operated, double-diaphragm pump to draw ready-to-use chemical from the 20 gallon tank. It injects compressed air into the solution to greatly increase volume and coverage ability and projects rich, clinging foam through the discharge hose, wand and fan nozzle.

Key Features

- Draws pre-diluted chemical from the 20 gallon tank
- Cost-effective Flojet AODD pump
- The chemical flow rate is regulated by the foamer body to match the mid-range of the air pump's specified operating range which protects the pump from running at maximum capacity
- Projects a usable volume of rich, clinging foam which increases chemical contact time and effectiveness
- Foaming expands the chemical and reduces over-application by providing visual assurance of coverage
- Fan pattern nozzle with 10' foam throw
- Covers up to 500 sq ft (46.5 sq m) in 2.5 minutes
- 16 minutes of foaming time per 20 gallons of solution
- Adjustable foam consistency (wet/dry)
- Chemical resistant wetted components ensure durability and years of reliable service
- Balanced weight distribution to prevent tipping
- Available with a 60 gallon tank (#941286)
- See other air-operated foamers and sprayers in [Catalog 4](#)

Includes

- Stainless steel 2-wheel cart with non-marking tires
- Lockable, stainless steel pump enclosure
- 20 gallon, wide-mouth, polyethylene chemical tank
- Air inlet ball valve and regulator/filter
- Flojet 1/4" AODD pump with Santoprene diaphragms
- Machined polypropylene pump-fed foamer body
- 40' discharge hose, stainless steel ball valve and polypropylene foam wand & fan nozzle

OPTIONS

Proportioning / Filling Options

| | |
|---|----------|
| 1-Way Ball Valve Mixing Station (4 GPM) | # 985100 |
| 1-Way Push Lever Mixing Station (4 GPM) | # 981100 |
| High Volume Mixing Station (9.9 GPM) | # 985835 |

Drain Foamer Attachment

| | |
|--|----------|
| Drain Foamer Attachment (Freedom, 2.5 & Liberty) | # 538245 |
|--|----------|

Alternate Air Pump Diaphragm - Santoprene Standard

| | |
|--|----------|
| Viton Diaphragm Upgrade For Flojet Air Pump | # 710756 |
| Kalrez Diaphragm Upgrade For Flojet Air Pump | # 710755 |

Stainless Steel Foam Wand (Upgrade)

| | |
|-----------------------------------|------------|
| Convert PP Wand to SS (New Units) | # 536603-X |
|-----------------------------------|------------|

APPLICATIONS

- Food & Beverage
- Agriculture/Horticulture
- Animal Health
- Industrial
- Pharm/Bio
- And Many Other Applications!

Optional
Drain
Foamer
Attachment



REQUIREMENTS

Ready-to-Use Chemical Solution

| | |
|----------------|---------------|
| Compressed Air | up to 6 CFM |
| Hose | 3/4" ID x 40' |
| Nozzle | 40150 |



Available with Color-Matched Tanks and Hoses

Lafferty
EQUIPMENT MANUFACTURING INC.

1.501.851.2820 or 1.800.999.2820
laffertyequipment.com